



Pin.No	Symbol	Level	Function
1	VSS	—	GND(0V)
2	VDD	—	Power Supply (+5V)
3	V0	—	Operating Voltage for LCD
4	RS	H/L	Hi: data ; L: Instruction code
5	R/W	H/L	H: read ; L: write
6	E	H/L	Enable Signal
7-14	DB0-DB7	H/L	Data Bus
15	A	—	Power supply for LED backlight (+5V)
16	K	—	Power supply for LED backlight (-)

ABSOLUTE MAXIMUM RATING			
Item	Symbol	Min	Max
Operating Voltage	VDD	4.7	5.0
Operating Current	I _{DD}	-	1.8
LED Voltage	V _{LED}	4.8	5.0
LED Current	I _{LED}	-	55
			60

- Description**
- 1.DISPLAY TYPE: STINNEGATIVE BLUE / (STINPOSITIVE YELLOW/GREEN)
 - 2.Viewing Direction: 6 O'CLOCK ; (12 O'CLOCK)
 - 3.Polarizer Mode: Transitive ; (Transflexive ; Reflective)
 - 4.Color of Backlight: White ; (Yellow/Green)
 - 5.Operating Temp: -20° ~ 70°C.
 - 6.Storage Temp: -30° ~ 80°C.
 - 7.Character Table: English; Japanese; European; Cyrillic.
 - 8.Operating Voltage Option: 5.0V or 3.3V.

REVISION RECORD		DATE	DATE
1			
2			
3			
4			
5			
6			

SHENZHEN ET TECHNOLOGY CO.,LTD.	www.eastel.com	E-mail: east@eastel.com
TITLE: LCM OUTLINE DIMENSION		
Model No.: ET-C0802CV3		
Part No.: SPEC-ET-C0802CV3	Pro.(3)	VER.: A
DRAWN	OY	DATE [2011.07.01] SHEET: 1/1
CHECKED		DATE
APPROVED		DATE
		SCALE: 1:1