



PIN	SYMBOL	PIN	SYMBOL
1	CS1	15	VOUT
2	RES	16	CAP3P
3	A0	17	CAP1N
4	WR	18	CAP1P
5	RD	19	CAP2P
6	D0	20	CAP2N
7	D1	21	V4
8	D2	22	V3
9	D3	23	V2
10	D4	24	V1
11	D5	25	V0
12	D6	26	C86
13	D7	27	P/S
14	VSS	28	VDD

NOTES:

1. DISPLAY TYPE: FSTN
2. OPERATING VOLTAGE: VOP:9.0V;VDD:3.0V
3. OPERATING TEMPERATURE: -20°C~70°C
4. STORAGE TEMPERATURE: -30°C~80°C
5. DRIVE MODE: 1/64D,1/9B
6. VIEWING DIRECTION: 12:00
7. POLARIZER TYPE: TRANSFLECTIVE, POSITIVE
8. CONNECTOR: COG
9. Driver IC: ST7565R

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
1			E-mail: east@eastel.com	
2			TITLE: LCM OUTLINE DIMENSION	
3			Model No.: ET-G12864-14	
4			Part No.: SPEC-G12864-14	
5			DRAWN: OU DATE: 2010.11.27	
6			CHECKED: DATE: SHEET: 1/1	
			APPROVED: DATE: UNIT: mm	
			SCALE: 1:1	