



NO.	Pin Name
1	VSS
2	A0
3	/WR
4	/RD
5	/CS
6	/RST
7	VDD
8	D0
9	D1
10	D2
11	D3
12	D4
13	D5
14	D6
15	D7
16	BLK
17	NC
18	BLA

- Note:
1. Display Type: FSTN
 2. View Direction: 6 0° Clock
 3. Polarizer Mode: Positive/Transflective
 4. Drive Method: 1/160 Duty, 1/14 Bias
 5. LCD drive voltage: 16.5V
 6. Logic Supply Voltage: 3.3V
 7. Operating Temperature: -20°C ~ +70°C
 8. Operating Temperature: -30°C ~ +80°C
 9. Backlight: LED White, VA=3.3V, If=90mA

REVISION RECORD		DATE
1		
2		
3		
4		
5		
6		

SHENZHEN ET TECHNOLOGY CO.,LTD.	
HTTP:// www.easetel.com	E-mail: east@easetel.com
TITLE: LCM OUTLINE DIMENSION	
Model No.: ET-G160160CV7	GEN.TOL.: ±0.2
Part No.: SPEC-ET-G160160CV7	PRO.(3):
DRAWN 欧阳路长	DATE 2012.04.19
CHECKED	DATE
APPROVED	DATE
VER.: A	SHEET: 1/1
	UNIT: mm
	SCALE: 1:1

