



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	RS	Data / Instruction select
5	RW	Read / write select
6	E	Enable signal
7-14	DB0-DB7	Data bus
15	/CS3	Chip select of U4 (Low effective)
16	/RST	Reset signal (Low effective)
17	/CS2	Chip select of U3 (Low effective)
18	/CS1	Chip select of U2 (Low effective)
19	Vout	Negative voltage output
20	A	Backlight anode (+5V)

ABSOLUTE MAXIMUM RATING			
Item	Symbol	Min	Max
Supply voltage logic	VDD	4.7	5.0
LCD Operating Voltage	VDD-V0	11.8	12.5
LED Voltage	VLED	4.8	5.0
LED Current	ILED	140	130
			160

- Description**
- 1.DISPLAY TYPE: STN/Positive Yellow-Green, (STN/Negative Blue/STN)
 - 2.Viewing Direction: 6 O'CLOCK : (12 O'CLOCK).
 - 3.Polarizer Model: Transmissive ; (Transmissive ; Reflective).
 - 4.Color of Backlight: Yellow/Green (White).
 - 5.Operating voltage option : 5V ; (3.3V)
 - 6.Operating Temp: -20° ~ -70° C
 - 7.Storage Temp: -30° ~ 80° C

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
A	First Issue		HTTPE:// www.eastel.com	E-mail: east@eastel.com
B			TITLE: LCM OUTLINE DIMENSION	GEN.TOL.: ±0.2
C			Model No.: ET-G19264AV4	PRO.(3):
D			Part No.: SPEC-ET-G19264AV4	VER.: A
E			DRAWN OY	DATE 2011.06.16
F			CHECKED	DATE
			APPROVED	DATE
				SCALE: 1:1