



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	RS	Data / Instruction select
5	R/W	Read / write select
6	E	Enable signal
7-14	DB0-DB7	Data bus
15	/CS1	Chip select of IC1 (Low effective)
16	/RST	Reset signal (Low effective)
17	/CS2	Chip select of IC2 (Low effective)
18	/CS3	Chip select of IC3 (Low effective)
19	Vout	Negative voltage output
20	A	Backlight anode (+5V)

ABSOLUTE MAXIMUM RATING					
Item	Symbol	Min	Type	Max	Unit
Supply voltage logic	VDD	4.7	5.0	5.2	V
LCD Operating Voltage	VDD-V0	11.8	12.5	13.85	V
LED Voltage	VLED	4.8	5.0	5.2	V
LED Current	ILED	-	500	-	mA

Description	
1	DISPLAY TYPE: STN / Positive yellow-Green, (STN / Negative Blue : Tsun )
2	Viewing Direction: 6 O'CLOCK : ( 12 O'CLOCK )
3	Polarizer Mode: Transmissive : ( Transmissive : Reflective )
4	Color of Backlight: Yellow/Green ( White )
5	Operating voltage option : 5V
6	Operating Temp: -20° ~ 70°C
7	Storage Temp: -30° ~ 80°C

REVISION RECORD		SHENZHEN ET TECHNOLOGY CO.,LTD.	
DATE	DATE	EMAIL: sash@esate.com	EMAIL: sash@esate.com
1		HTTP://www.esate.com	GEN.TOL.: 40.2
2		TITLE: LCD OUTLINE DIMENSION	PROJ.09: 1
3		Model No.: ET-G19264B2	VER.: A
4		Part No.: SPEC-ET-G19264B2	DRAWN OY
5		CHECKED	DATE 2011.06.18
6		APPROVED	DATE
			SCALE: 1:1

A

由 Autodesk 教育版产品制作

D

1

2

3

4

5

6

7

8

A

B

C

D