



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	RS	Data / Instruction select
5	R/W	Read / write select
6	E	Enable signal
7-14	DB0-DB7	Data bus
15	/CS1	Chip select of U2 (Low effective)
16	/RST	Reset signal (Low effective)
17	/CS2	Chip select of U3 (Low effective)
18	/CS3	Chip select of U4 (Low effective)
19	Vout	Negative voltage output
20	A	Backlight anode (+5V)

ABSOLUTE MAXIMUM RATING				
Item	Symbol	Min	Type	Max
Supply voltage logic	VDD	4.7	5.0	5.2
LCD Operating Voltage	VDD-V0	11.8	12.5	13.85
LED Voltage	VLED	4.8	5.0	5.2
LED Current (Side LED)	ILED	140	150	160

- Description**
- 1) DISPLAY TYPE: STN / Positive Yellow-Green; (STN / Negative Blue; Fsin)
 - 2) Viewing Direction: 6 O'CLOCK; (12 O'CLOCK)
 - 3) Polarizer Mode: Transmissive; (Transmissive; Reflective)
 - 4) Color of Backlight: Yellow/Green; (White)
 - 5) Operating voltage option: 5V; (3.3V)
 - 6) Operating Temp: -20° ~ 70° C
 - 7) Storage Temp: -30° ~ 80° C

REVISION RECORD		SHENZHEN ET TECHNOLOGY CO.,LTD.	
A	DATE	HTTIP:// www.eastel.com	E-mail: east@eastel.com
A	First Issue	Model No.: ET-G19264BV3	GEN.TOL.: ±0.2
B		Part No.: SPEC-ET-G19264BV3	PRO.(3): A
C		DRAWN OY	DATE 2011.06.18
D		CHECKED	DATE
E		APPROVED	DATE
F			SCALE: 1:1