



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	Vout	Negative voltage output
5	RS	Data / instruction select
6	R/W	Read / write select
7	E	Enable signal
8-15	DB0-DB7	Data bus
16	/CS1	Chip select of U2 (Low effective)
17	/CS2	Chip select of U3 (Low effective)
18	/CS3	Chip select of U4 (Low effective)
19	/RST	Reset signal (Low effective)
20	A	Backlight anode (+5V)
21	K	Backlight cathode (+0V)

ABSOLUTE MAXIMUM RATINGS					
Item	Symbol	Min	Type	Max	Unit
Supply voltage logic	VDD	4.7	5.0	5.2	V
LCD Operating Voltage	VDD-V0	11.8	12.5	13.85	V
LED Voltage	VLED	4.8	5.0	5.2	V
LED Current (Side LED)	ILED	-	500	-	mA

- Description**
- 1.DISPLAY TYPE: STN/Positive Yellow-Green; (STN/Negative Blue; Tsun).
 - 2.Viewing Direction: 6 O'CLOCK; (12 O'CLOCK).
 - 3.Polarizer Mode: Transmissive; (Transmissive; Reflective).
 - 4.Color of Backlight: Yellow/Green; (White).
 - 5.Operating voltage option: 5V; (3.3V).
 - 6.Operating Temp: -20° ~ 70°C
 - 7.Storage Temp: -30° ~ 80°C

REVISION RECORD		DATE	DESCRIPTION	PROJ. NO.	VER.
1			TITLE: LCD OUTLINE DIMENSION	GEN.TOL.: ±0.2	A
2			Model No.: ET-G19264B/V4		
3			Part No.: SPEC-ET-G19264B/V4		
4			DRAWN: OY	DATE: 2011.06.17	SHEET: 1/1
5			CHECKED:	DATE:	UNIT: mm
6			APPROVED:	DATE:	SCALE: 1:1

SHENZHEN ET TECHNOLOGY CO.,LTD.
[HTTP://WWW.ET.COM](http://www.et.com)
 Email: eae@easetel.com