



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	RS	Data / Instruction select
5	R/W	Read / write select
6	E	Enable signal
7-14	DB0-DB7	Data bus
15	/CS1	Chip select of U2 (Low effective)
16	/RST	Reset signal (Low effective)
17	/CS2	Chip select of U3 (Low effective)
18	/CS3	Chip select of U4 (Low effective)
19	Vout	Negative voltage output
20	A	Backlight anode (+5V)

ABSOLUTE MAXIMUM RATING					
Item	Symbol	Min	Type	Max	Unit
Supply voltage logic	VDD	4.7		5.0	5.2 V
LCD Operating Voltage	VDD-V0	11.8		12.5	13.85 V
LED Voltage	VLED	4.8		5.0	5.2 V
LED Current (Side LED)	ILED	60		100	120 mA

- Description**
- 1.DISPLAY TYPE: STN/Negative Blue; (STN/Positive Yellow-Green;Fsm).
 - 2.Viewing Direction: 6 O'CLOCK : (12 O'CLOCK).
 - 3.Polarizer Mode: Transmissive ; (Transflective).
 - 4.Color of Backlight: White; (Yellow/Green).
 5. Operating voltage option : 5V ;
 - 6.Operating Temp: -20° ~ 70° C
 - 7.Storage Temp: -30° ~ 80° C

REVISION RECORD		DATE		SHENZHEN ET TECHNOLOGY CO.,LTD.	
A	First Issue	HTTIP:// www.eastel.com	E-mail: east@eastel.com	GEN.TOL.: ±0.2	
B		Model No.: ET-G19264BV6		PRO.(3):	
C		Part No.: SPEC-ET-G19264BV6		VER.:	A
D		DRAWN OY	DATE 2011.06.18	SHEET:	1/1
E		CHECKED	DATE	UNIT:	mm
F		APPROVED	DATE	SCALE:	1:1