



Pin.No	Symbol	Description			
1	VSS	GND			
2	VDD	Power supply(+5V).			
3	V0	Operating voltage for LCD			
4	RS	Data / Instruction select			
5	R/W	Read / write select			
6	E	Enable signal			
7-14	DB0 - DB7	Data bus			
15	CS1	Chip selection			
16	/RST	Reset signal (Low effective)			
17	CS2	Chip selection			
18	CS3	Left half	CS3	CS2	CS1
		Right half	0	0	1
19	Vout	Chip selection	0	1	0
		Right half	0	1	0
20	A	Negative voltage output Backlight anode (+5V)	1	x	x

ABSOLUTE MAXIMUM RATING					
Item	Symbol	Min	Type	Max	Unit
Supply voltage logic	VDD	4.7	5.0	5.2	V
LCD Operating Voltage	VDD-V0	11.8	12.5	13.85	V
LED Voltage	VLED	4.8	5.0	5.2	V
LED Current	ILED	-	40	60	mA

- Description**
- 1.DISPLAY TYPE: FSTN/Positive/STN/Negative Blue).
 - 2.Viewing Direction: 6 D/CLOCK (12 D/CLOCK).
 - 3.Polarizer Mode: Transmissive.
 - 4.Color of Backlight: White.
 - 5.Operating voltage option : 5V J (3.3V)
 - 6.Operating Temp: -20° ~ 70°C
 - 7.Storage Temp: -30° ~ 80°C

REVISION RECORD		DATE	DESCRIPTION
1			GEN.TOL.: ±0.2
2			PRO.CB:
3			VER.: A
4			SHEET: 1/3
5			UNIT: mm
6			SCALE: 1:1

SHENZHEN ET TECHNOLOGY CO.,LTD.
<http://www.et.com>
 Email: eae@et.com

