



Pin.No	Symbol	Description
1	VSS	GND
2	VDD	Power supply for logic and LCD
3	V0	Operating voltage for LCD
4	/RST	Reset signal ( Low effective )
5	CS	Chip Select
6	SID	Serial data input.
7	SCLK1	Serial clock.
8	SCLK2	Serial clock.
9	A	Backlight anode(+5V).
10	K	Backlight cathode(+V).
11	LED1	LED1 anode input.
12	LED2	LED2 anode input.
13	LED3	LED3 anode input.
14	LEDK	LED cathode input.

ABSOLUTE MAXIMUM RATING					
Item	Symbol	Type	Unit		
Supply voltage logic	VDD	4.7	5.0	5.2	V
LCD Operating Voltage	VDD-V0	11.8	12.5	13.85	V
LED Voltage	VLED	4.8	5.0	5.2	V
LED Current	ILED	-	200	-	mA

- Description**
1. DISPLAY TYPE: STN / Positive Yellow-Green. ( STN / Negative Blue. Fstn ).
  2. Viewing Direction: 6 O'CLOCK : ( 12 O'CLOCK ).
  3. Polarizer Mode: Transflective ; ( Transitive ; Reflective ).
  4. Color of Backlight: Yellow/Green; ( White ).
  5. Operating voltage option : 3.3V~ 5V
  6. Operating Temp: -10° ~ 50°C
  7. Storage Temp: -20° ~ 70°C
  8. Display Driver: ST7920+ST7921

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
			HTTP://www.et.com	Email: eae@et.com
1	TITLE: LCM OUTLINE DIMENSION		GEN.TOL.: ±0.2	
2			Model No.: ET-G1926DV1	PROJ.03
3			Part No.: SPEC-ET-G1926DV1	VER.: A
4	DRAWN	DATE	2011.06.20	SHEET: 1/1
5	CHECKED	DATE		UNIT: mm
6	APPROVED	DATE		SCALE: 1:1