



DISPLAY TYPE: STN/NEGATIVE BLUE
 VIEWING DIRECTION: 6:00
 POLARIZER MODE: TRANSMISSIVE
 DRIVING METHOD: 1/240DUTY 1/17BIAS
 OPERATING VOLTAGE: 5.0V
 OPERATING TEMPERATURE: -20° ~ 70°C
 STORAGE TEMPERATURE: -30°~80°C
 BACK LIGHT: CCFL/WHITE

J1 (16PIN Pitch: 2.54mm)	J2 (20 PIN Pitch: 2.54mm)	J3 (16PIN Pitch: 2.54mm)	J4 (24 PIN Pitch: 1.0mm)	J5 (22 PIN Pitch: 1.0mm)	J6 (2 PIN Pitch: 1.0mm)	J9 (4PIN)
No.	No.	No.	No.	No.	No.	No.
Name	Name	Name	Name	Name	Name	Name
1 D0	1 VSS	1 D0	17 VO	1 VSS	1 Y+	1 Y+
2 D1	2 VDD	2 D1	18 TCLK	2 VDD	2 X+	2 X+
3 D2	3 VO	3 D2	19 D0	3 VO	3 Y-	3 Y-
4 D3	4 VSS	4 D3	20 TCS	4 VSS	4 X-	4 X-
5 D3SPOFF	5 RST	5 D3SPOFF	21 TCS	5 RST		
6 FILM	6 VCS	6 FILM	22 TINT	6 RST		
7 M	7 AO	7 M	23 LEDA	7 DB0		
8 LP	8 RST	8 LP	24 LEDK	8 DB1		
9 CP	9 DB0	9 CP		9 DB2		
10 VDD	10 DB1	10 VDD		10 DB3		
11 VSS	11 DB2	11 VSS		11 DB4		
12 VEE	12 DB3	12 VEE		12 DB5		
13 VO	13 DB4	13 VO		13 DB6		
14 FGND	14 DB5	14 FGND		14 DB7		
15 DB6	15 VSS	15 DB6		15 VSS		
16 DB7	16 VEE	16 DB7		16 VEE		

REVISION RECORD		DATE	DATE	DATE	DATE	DATE
1						
2	TITLE, LCM OUTLINE DIMENSION					
3	Model No.: ET-G320240CV1					
4	Part No.: SPEC-ET-G320240CV1-BGSWCMT					
5	DRAWN OY	DATE	2011.06.07	SHEET:	1/1	UNIT: mm
6	CHECKED	DATE		APPROVED		SCALE: 1:1

SHENZHEN ET TECHNOLOGY CO.,LTD.
 E-mail: east@eastel.com
 GEN.TOL.:±0.2
 PRO.03: A
 VER.: A
 DATE: 2011.06.07
 SHEET: 1/1
 UNIT: mm
 SCALE: 1:1