



J3(20PIN,2.54mm)		J2(22PIN,1.0mm)		J1(24PIN,1.0mm)	
No.	Name	No.	Name	No.	Name
1	VSS	1	VSS	1	/RST
2	VDD	2	VDD	2	/RD
3	V0	3	V0	3	/WR
4	/WR	4	A0	4	/CS
5	/RD	5	/WR	5	A0
6	/CS	6	/RD	6	DB0
7	A0	7	DB0	7	DB1
8	/RST	8	DB1	8	DB2
9	DB0	9	DB2	9	DB3
10	DB1	10	DB3	10	DB4
11	DB2	11	DB4	11	DB5
12	DB3	12	DB5	12	DB6
13	DB4	13	DB6	13	DB7
14	DB5	14	DB7	14	VDD
15	DB6	15	/CS	15	VSS
16	DB7	16	/RST	16	VEE
17	LEDA	17	VEE	17	V0
18	VEE	18	SEL	18	T-CL
19	LEDA	19	INC	19	T-DO
20	LEDK	20	INC	20	T-DI
		21	INC	21	T-CS
		22	INC	22	T-INT
				23	INC
				24	INC

0.33			
0.36			
0.3			
0.3			

- NOTES:
1. DISPLAY TYPE: STN/BLUE MODE
  2. VIEWING DIRECTION: 6:00
  3. POLARIZER MODE: TRANSMISSIVE/NEGATIVE
  4. DRIVE METHOD: 1/240 DUTY 1/16 BIAS
  5. OPERATING VOLTAGE: 5.0V
  6. OPERATING TEMP: -20°C~+70°C
  7. STORAGE TEMP: -30°C~+80°C
  8. CONNECTOR: TAB
  9. DRIVER IC: RA8835

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
			HTTP://www.eastet.com	E-mail: east@eastet.com
1			TITLE: LCM OUTLINE DIMENSION	GEN.TOL.:±0.2
2			Model No.: ET-G320240EV1	PRO.(3):
3			Part No.: ET-G320240EV1-BCS/WSWT	VER.: A
4			DRAWN OY	DATE 2011.06.07
5			CHECKED	DATE
6			APPROVED	DATE