



J1:10PIN,P1mm

PIN	SYMBLE
1	GND
2	GND
3	GND
4	BUSY
5	TXD
6	RXD
7	IO0
8	VCC
9	VCC
10	VCC

J2:8PIN,P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	DIN
4	DIN
5	DOUT
6	BUSY
7	VCC
8	VCC

J8:4PIN,P2.54mm

PIN	SYMBLE
1	GND
2	TXD
3	RXD
4	VDC

J6:5PIN,P2.54mm

PIN	SYMBLE
1	GND
2	TCK
3	TMS
4	TDI
5	TDO

J7:16PIN,P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	VIN
4	P3.7
5	P1.0
6	P3.5
7	P1.1
8	P3.4
9	P1.2
10	P3.3
11	P1.3
12	P3.2
13	P1.4
14	P1.7
15	P1.5
16	P1.6

J9:12PIN,P2.54mm

PIN	SYMBLE
1	KEY8
2	KEY7
3	KEY6
4	KEY5
5	KEY4
6	KEY3
7	KEY2
8	KEY1
9	KP1
10	KP0
11	VIN
12	GND

NOTES:
 1.Display type:5.7" TFT
 2.Viewing direction:12 O'CLOCK
 3.Operation temperature:-20°C~+70°C
 4.Storage temperature:-30°C~+80°C
 5.Operating Voltage:3.3V~6V
 6.Tolerance is ±0.3 unless otherwise noted

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
A		First Issue	E-mail: east@eastet.com	
B		PCB update V2.0	GEN.TOL.: ±0.2	
C		YNS,2013-7-8	TITLE: ET-HMI	
D		JLS,2013-12-30	Model No.: ET-T640480-057	
E			Part No.: SPEC-ET-T640480-05702WN	
F			VER.: A	
			DRAWN	JLS
			DATE	2013-12-30
			CHECKED	DATE
			APPROVED	DATE
				SHEET: 1
				UNIT: mm
				SCALE: 1:1