



- NOTES:**
1. Display type: 7.0" TFT;
 2. Viewing direction: 6 O'CLOCK;
 3. Polarizer mode: Transmissive;
 4. Operation temperature: -20°C ~ +70°C;
 5. Storage temperature: -30°C ~ +80°C;
 6. Operating Voltage: 5V;
 7. Tolerance is ±0.3 unless otherwise noted.

J1: 10PIN, P1mm

PIN	SYMBLE
1	GND
2	GND
3	GND
4	BUSY
5	TXD
6	RXD
7	IOO
8	+5V
9	+5V
10	+5V

J2: 5PIN, P2mm

PIN	SYMBLE
1	+5V
2	RXD
3	BUSY
4	GND
5	TXD

J3: 5PIN, P2.54mm

PIN	SYMBLE
1	+5V
2	RXD
3	BUSY
4	GND
5	TXD

J4: 5PIN, P2.54mm

PIN	SYMBLE
1	GND
2	TCK
3	TMS
4	TDI
5	TDO

J5: 8PIN, P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	DIN
4	DIN
5	DOUT
6	BUSY
7	VCC
8	VCC

尔泰科技
 2013.12.21
 发行章

编码: 994320102

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
A		FIRST ISSUE	E-mail: east@eastet.com	
B			TITLE: ET-HMI	GEN.TOL.: ±0.2
C			Model No.: ET-T800480-070	PRO.(3):
D			Part No.: SPEC-ET-T800480-07001WT	VER.: A
E			DRAWN: JLS	DATE: 2013-11-22
F			CHECKED:	SHEET: 1/1
			APPROVED:	UNIT: mm
				SCALE: 1:1