



- NOTES:**
1. Display type: 7.0" TFT;
  2. Viewing direction: 6 O'CLOCK;
  3. Polarizer mode: Transmissive;
  4. Operation temperature: -20°C ~ +70°C;
  5. Storage temperature: -30°C ~ +80°C;
  6. Operating Voltage: 3.6~6.0V OR 6V~42V;
  7. Tolerance is ±0.3 unless otherwise noted.

**J1: 10PIN, P1mm**

PIN	SYMBLE
1	GND
2	GND
3	GND
4	BUSY
5	TXD
6	RXD
7	IO0
8	VIN
9	VIN
10	VIN

**J2: 5PIN, P2mm**

PIN	SYMBLE
1	TXD
2	GND
3	BUSY
4	RXD
5	VIN

**J3: 5PIN, P2.54mm**

PIN	SYMBLE
1	VIN
2	RXD
3	BUSY
4	GND
5	TXD

**J4: 5PIN, P2.54mm**

PIN	SYMBLE
1	GND
2	TCK
3	TMS
4	TDI
5	TDO

**J11: 8PIN, P2.54mm**

PIN	SYMBLE
1	VCC
2	VCC
3	BUSY
4	DOUT
5	DIN
6	DIN
7	GND
8	GND

**J8: 16PIN, P2.54mm**

PIN	SYMBLE
1	GND
2	GND
3	VIN
4	P3.7
5	P1.0
6	P3.5
7	P1.1
8	P3.4
9	P1.2
10	P3.3
11	P1.3
12	P3.2
13	P1.4
14	P1.7
15	P1.5
16	P1.6

**J9: 12PIN, P2.54mm**

PIN	SYMBLE
1	KEY8
2	KEY7
3	KEY6
4	KEY5
5	KEY4
6	KEY3
7	KEY2
8	KEY1
9	KP1
10	KP0
11	VCC
12	GND

**J10: 4PIN, P2.54mm**

PIN	SYMBLE
1	GND
2	TXD
3	RXD
4	VDC

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
			E-mail: east@eastet.com	
A	FIRST ISSUE		TITLE: ET-HMI	GEN.TOL.: ±0.2
B	变更操作电压	2014.04.01	Model No.: ET-T800480-070	PRO.(3):
C			Part No.: SPEC-ET-T800480-07003WT	VER.SN A
D			DRAWN YSN	DATE 2013-10-6
E			CHECKED	SHEET: 1/1
F			APPROVED	UNIT: mm
			DATE	SCALE: 1:1