



- NOTES:**
1. Display type: 7.0" TFT;
 2. Viewing direction: 6 O'CLOCK;
 3. Polarizer mode: Transmissive;
 4. Operation temperature: -20°C ~ +70°C;
 5. Storage temperature: -30°C ~ +80°C;
 6. Operating Voltage: 3.6~6.0V OR 6V~42V;
 7. Tolerance is ±0.3 unless otherwise noted.

J1: 10PIN, P1mm

PIN	SYMBLE
1	GND
2	GND
3	GND
4	BUSY
5	TXD
6	RXD
7	IO0
8	VIN
9	VIN
10	VIN

J5: 8PIN, P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	DIN
4	DIN
5	DOUK
6	BUSY
7	VCC
8	VCC

J3: 5PIN, P2.54mm

PIN	SYMBLE
1	GND
2	TCK
3	TMS
4	TDI
5	TDO

J4: 16PIN, P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	VIN
4	P3.7
5	P1.0
6	P3.5
7	P1.1
8	P3.4
9	P1.2
10	P3.3
11	P1.3
12	P3.2
13	P1.4
14	P1.7
15	P1.5
16	P1.6

J5: 12PIN, P2.54mm

PIN	SYMBLE
1	KEY8
2	KEY7
3	KEY6
4	KEY5
5	KEY4
6	KEY3
7	KEY2
8	KEY1
9	KP1
10	KP0
11	VCC
12	GND

J6: 4PIN, P2.54mm

PIN	SYMBLE
1	GND
2	TXD
3	RXD
4	VDC

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
A		FIRST ISSUE	E-mail: east@eastet.com	
B		变更操作电压	2014.04.01	Model No.: ET-T800480-070
C			Part No.: SPEC-ET-T800480-07004WN	VER.: A
D		DRAWN	JLS	DATE 2013-11-23
E		CHECKED		SHEET: 1
F		APPROVED		UNIT: mm
			DATE	SCALE: 1:1