



J1:8PIN,P2.54mm	
PIN	SYMBLE
1	GND
2	GND
3	DIN
4	DIN
5	DOUT
6	BUSY
7	VCC
8	VCC

J3:5PIN,P2.54mm	
PIN	SYMBLE
1	RESET
2	GND
3	SWCLK
4	SWDIO
5	VCC

J4:5PIN,P2.54mm	
PIN	SYMBLE
1	GND
2	TCK
3	TMS
4	TDI
5	TDO

J6:4PIN,P1mm	
PIN	SYMBLE
1	X-
2	Y-
3	X+
4	Y+

NOTES:

1. Display type:7.0" TFT;
2. Viewing direction:6 O'CLOCK;
3. Polarizer mode:Transmissive;
4. Operation temperature:-20°C~+70°C;
5. Storage temperature:-30°C~+80°C;
6. Operating Voltage:5V;
7. Tolerance is ±0.3 unless otherwise noted.

REVISION RECORD		DATE	SHENZHEN ET TECHNOLOGY CO.,LTD.	
A		FIRST ISSUE	E-mail: east@eastet.com	
B			TITLE: ET-HMI	GEN.TOL.: ±0.2
C			Model No.: ET-T800480-070	PRO.(3):
D			Part No.: SPEC-ET-T800480-07005WN	VER.: A
E			DRAWN: JLS	DATE: 2014-03-15
F			CHECKED:	SHEET: 1/1
			APPROVED:	UNIT: mm
				SCALE: 1:1