



J1:10PIN,P1mm

PIN	SYMBLE
1	GND
2	GND
3	GND
4	BUSY
5	TXD
6	RXD
7	IOO
8	VIN
9	VIN
10	VIN

J2:8PIN,P2.54mm

PIN	SYMBLE
1	GND
2	GND
3	DIN
4	DIN
5	DOUT
6	BUSY
7	VIN
8	VIN

J3:8PIN,P2.54mm

PIN	SYMBLE
1	DATA+
2	DATA-
3	GND

J9:18PIN,P2.54mm

PIN	SYMBLE	PIN	SYMBLE
1	GND	10	P2.25
2	GND	11	P2.23
3	VIN	12	P4.21
4	P4.7	13	P1.18
5	P4.22	14	P2.10
6	P4.23	15	P4.16
7	P4.26	16	P2.22
8	P2.22	17	P2.15
9	P2.26	18	P2.14

NOTES:

1. Display type: 10.4" TFT
2. Viewing direction: 6 O'CLOCK
3. Operation temperature: -20°C ~ +70°C
4. Storage temperature: -30°C ~ +80°C
5. Operating Voltage: 3.3~6V
6. Tolerance is ±0.3 unless otherwise noted

REVISION RECORD	DATE	SHENZHEN ET TECHNOLOGY CO.,LTD. E-mail: east@eastet.com	
A	First Issue	TITLE: ET-HMI GEN.TOL.: ±0.2	
B		Model No.: ET-T800600-104 PRO.(3):	
C		Part No.: SPEC-ET-T800600-10401WN VER.: A	
D		DRAWN: JLS	DATE: 2014-04-01 SHEET: 1
E		CHECKED:	DATE: UNIT: mm
F		APPROVED:	DATE: SCALE: 1:1